



Sun Ray™ Connector for Windows OS, Version 1.0 Release Notes

Sun Microsystems, Inc.
www.sun.com

Part No. 819-4667-11
May 2006, Revision A

Copyright 2005, 2006, Sun Microsystems, Inc., 4150 Network Circle, Santa Clara, California 95054, U.S.A. All rights reserved.

Sun Microsystems, Inc. has intellectual property rights relating to technology embodied in the product that is described in this document. In particular, and without limitation, these intellectual property rights may include one or more of the U.S. patents listed at <http://www.sun.com/patents>, and one or more additional patents or pending patent applications in the U.S. and in other countries.

This document and the product to which it pertains are distributed under licenses restricting their use, copying, distribution, and decompilation. No part of the product or of this document may be reproduced in any form by any means without prior written authorization of Sun and its licensors, if any.

Third-party software, including font technology, is copyrighted and licensed from Sun suppliers.

Parts of the product may be derived from Berkeley BSD systems, licensed from the University of California. UNIX is a registered trademark in the U.S. and other countries, exclusively licensed through X/Open Company, Ltd.

Sun, Sun Microsystems, the Sun logo, Sun Ray, Sun Ray Connector for Windows OS, Sun WebServer, Sun Enterprise, Ultra, UltraSPARC, Sun Java Desktop System, SunFastEthernet, Sun Quad FastEthernet, Java, JDK, HotJava, Solaris, and the Appliance Link Protocol (ALP) are trademarks, registered trademarks, or service marks of Sun Microsystems, Inc. in the U.S. and other countries. All SPARC trademarks are used under license and are trademarks or registered trademarks of SPARC International, Inc. in the U.S. and other countries. Products bearing SPARC trademarks are based upon an architecture developed by Sun Microsystems, Inc.

Netscape is a trademark or registered trademark of Netscape Communications Corporation.

The OPEN LOOK and Sun™ Graphical User Interface was developed by Sun Microsystems, Inc. for its users and licensees. Sun acknowledges the pioneering efforts of Xerox in researching and developing the concept of visual or graphical user interfaces for the computer industry. Sun holds a non-exclusive license from Xerox to the Xerox Graphical User Interface, which license also covers Sun's licensees who implement OPEN LOOK GUIs and otherwise comply with Sun's written license agreements.

Federal Acquisitions: Commercial Software—Government Users Subject to Standard License Terms and Conditions.

Use, duplication, or disclosure by the U.S. Government is subject to restrictions set forth in the Sun Microsystems, Inc. license agreements and as provided in DFARS 227.7202-1(a) and 227.7202-3(a) (1995), DFARS 252.227-7013(c)(1)(ii) (Oct. 1998), FAR 12.212(a) (1995), FAR 52.227-19, or FAR 52.227-14 (ALT III), as applicable.

DOCUMENTATION IS PROVIDED "AS IS" AND ALL EXPRESS OR IMPLIED CONDITIONS, REPRESENTATIONS AND WARRANTIES, INCLUDING ANY IMPLIED WARRANTY OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR NON-INFRINGEMENT, ARE DISCLAIMED, EXCEPT TO THE EXTENT THAT SUCH DISCLAIMERS ARE HELD TO BE LEGALLY INVALID.

Copyright 2005, 2006, Sun Microsystems, Inc., 4150 Network Circle, Santa Clara, California 95054, Etats-Unis. Tous droits réservés.

Sun Microsystems, Inc. a les droits de propriété intellectuels relatifs à la technologie incorporée dans le produit qui est décrit dans ce document. En particulier, et sans la limitation, ces droits de propriété intellectuels peuvent inclure un ou plus des brevets américains énumérés à <http://www.sun.com/patents> et un ou les brevets plus supplémentaires ou les applications de brevet en attente dans les Etats-Unis et dans les autres pays.

Ce produit ou document est protégé par un copyright et distribué avec des licences qui en restreignent l'utilisation, la copie, la distribution, et la décompilation. Aucune partie de ce produit ou document ne peut être reproduite sous aucune forme, par quelque moyen que ce soit, sans l'autorisation préalable et écrite de Sun et de ses bailleurs de licence, s'il y ena.

Le logiciel détenu par des tiers, et qui comprend la technologie relative aux polices de caractères, est protégé par un copyright et licencié par des fournisseurs de Sun.

Des parties de ce produit pourront être dérivées des systèmes Berkeley BSD licenciés par l'Université de Californie. UNIX est une marque déposée aux Etats-Unis et dans d'autres pays et licenciée exclusivement par X/Open Company, Ltd.

Sun, Sun Microsystems, le logo Sun, Sun Ray, Sun Ray Connector for Windows OS, Sun WebServer, Sun Enterprise, Ultra, UltraSPARC, Sun Java Desktop System, SunFastEthernet, Sun Quad FastEthernet, Java, JDK, HotJava, Solaris et Appliance Link Protocol (ALP) sont des marques de fabrique ou des marques déposées, ou marques de service, de Sun Microsystems, Inc. aux Etats-Unis et dans d'autres pays.

Toutes les marques SPARC sont utilisées sous licence et sont des marques de fabrique ou des marques déposées de SPARC International, Inc. aux Etats-Unis et dans d'autres pays. Les produits portant les marques SPARC sont basés sur une architecture développée par Sun Microsystems, Inc.

Netscape est une marque de Netscape Communications Corporation aux Etats-Unis et dans d'autres pays.

L'interface d'utilisation graphique OPEN LOOK et Sun™ a été développée par Sun Microsystems, Inc. pour ses utilisateurs et licenciés. Sun reconnaît les efforts de pionniers de Xerox pour la recherche et le développement du concept des interfaces d'utilisation visuelle ou graphique pour l'industrie de l'informatique. Sun détient une licence non exclusive de Xerox sur l'interface d'utilisation graphique Xerox, cette licence couvrant également les licenciées de Sun qui mettent en place l'interface d'utilisation graphique OPEN LOOK et qui en outre se conforment aux licences écrites de Sun.

LA DOCUMENTATION EST FOURNIE "EN L'ETAT" ET TOUTES AUTRES CONDITIONS, DECLARATIONS ET GARANTIES EXPRESSES OU TACITES SONT FORMELLEMENT EXCLUES, DANS LA MESURE AUTORISEE PAR LA LOI APPLICABLE, Y COMPRIS NOTAMMENT TOUTE GARANTIE IMPLICITE RELATIVE A LA QUALITE MARCHANDE, A L'APTITUDE A UNE UTILISATION PARTICULIERE OU A L'ABSENCE DE CONTREFAÇON.



Adobe PostScript

Contents

| | |
|--|---|
| Recommended Patches | 1 |
| SRSS 3.1 Patch Dependency and Availability | 2 |
| Additional Recommended Patches | 2 |
| Trusted Solaris TM | 2 |
| Japanese Keyboard Patch | 3 |
| OpenSSL Libraries | 3 |
| Known Issues | 3 |
| Trusted Solaris Limitations | 8 |
| Windows Limitations | 8 |
| Documentation | 9 |
| L10N Documentation Errata | 9 |
| Trusted Solaris Configuration | 9 |
| Description of Sun Ray Connector Compression | 9 |
| Description of <code>uttscwrap</code> | 9 |

Sun Ray Connector for Windows OS Release Notes

The Sun Ray™ Connector for Windows OS is a Sun-supported, Microsoft-certified terminal services client based on the Microsoft Remote Desktop Protocol (RDP) Version 5.2. It is described in the *Sun Ray Connector for Windows OS Installation and Administration Guide*. For convenience, the Sun Ray Connector for Windows OS is often called the Sun Ray Connector.

Recommended Patches

Please ensure that the latest recommended patch clusters are installed on the Sun Ray server.

SRSS 3.1 Patch Dependency and Availability

This release depends on the -03 revision of the Sun Ray Server Software 3.1 patch, which enables the Sun Ray Connector to work correctly on all supported platforms. It is located in the Patches section of the Sun Ray Server Software 3.1 release image in the Sun Ray Software 4 release. Please ensure that this patch (or later) is installed on your system.

TABLE 1 SRSS 3.1 Patch Numbers for Sun Ray Connector

| Operating System/Platform | Patch Number |
|---------------------------|--------------|
| Solaris SPARC | 120879-03 |
| Solaris x86 | 120880-03 |
| Linux | 120881-03 |

Additional Recommended Patches

The following patches fix an Xsun memory leak issue that affects Sun Ray performance:

TABLE 2 Patches for Xsun Memory Leaks

| Operating System/Platform | Patch Number |
|---------------------------|--------------------|
| Solaris 9 | 112785-49 or later |
| Solaris 10 SPARC | 119059-13 |
| Solaris 10 X86 | 119060-12 |

Trusted Solaris™

The following patch enables shortcut keys on the local desktop manager to work correctly:

TABLE 3 Patches for Trusted Solaris

| Operating System/Platform | Patch Number |
|---------------------------|--------------|
| Trusted Solaris 2/04 | 121545-03 |

Japanese Keyboard Patch

The following patches enable correct behavior for Japanese language keyboards:

TABLE 4 Keyboard Patches for JA Locale

| Operating System/Platform | Patch Number |
|---------------------------|--------------|
| Solaris 8 SPARC | 111075-05 |
| Solaris 9 SPARC | 113764-04 |

OpenSSL Libraries

The Sun Ray Connector depends on the OpenSSL libraries, which must be installed in order for the Sun Ray Connector to work properly. For your convenience, the versions required for Solaris 8 and Solaris 9 platforms, and the libgcc packages upon which the OpenSSL libraries depend, are included in the Supplemental section of the release image. On all other supported platforms, the required versions are installed by default.

Known Issues

The latest known bugs and other issues are listed here, along with appropriate workarounds when they are available.

Note on Authentication Behavior

If the `-r scard` and `-u/-p` options are used together on the command line for `uttsc`, then the username/password options take precedence over smart card authentication, and the user is presented with the username login rather than a PIN prompt window.

Bug ID 6345509

The cut and paste menu options do not work correctly in transfers from OpenOffice from a Sun Ray session to a Windows application.

The issues have been identified as related to StarOffice, and appropriate bugs have been logged.

The workaround is to use **Ctrl-C** and **Ctrl-V** instead of menu options to perform these operations.

Bug ID 6358380

Serial port redirection does not work properly when more than one serial port is redirected.

Bug ID 6359564

If all the following conditions are present, the user is presented with a black screen upon hotdesking:

- CDE as the desktop manager on Solaris
- Sun Ray Connector in full screen mode (i.e., using the **-m** option)
- Screen lock enabled

The workaround is type the user's password blindly to unlock the screen, even though the screen lock is not presented. This causes the session to display correctly.

Bug ID 6360175

Some screensavers that are part of Windows 2000 contain a lot of animation. Sun Ray Windows Connector sessions running Windows 2000 screensavers can overload the Sun Ray server CPU (the Sun Ray Connector and the X server show high CPU usage). This problem appears on Solaris 8 only.

The way to solve this problem is to not use these screensavers in user sessions. Please consult the Windows documentation for information on how to disable screensavers for Terminal Services sessions.

Bug ID 6361417

In certain scenarios, redirecting serial ports to a Windows Terminal Server can consume up to 99% of the Sun Ray server's CPU.

Bug ID 6363133

Once a copy and paste operation has been performed, subsequent copy and paste operations from the same dtterm window to a Windows application always show the data from the first such operation.

Bug ID 6369558

uttscrewrap does not save the credentials between desktop sessions (that is, the “save password in keyring” option does not work). This bug in the Java Desktop System is fixed in Solaris 10 Update 2. Users who do not want to upgrade to Update 2 need to install patch 122212-02 for SPARC or 122213-02 for Intel when it is released. It is being tested at the moment.

Bug ID 6382123

Windows and Red Hat lock screens behave differently with the -m option of uttsc because of underlying issues with the Red Hat xscreensaver application. These issues sometimes make it possible, if an editor is open on the Windows session, to see the password in the clear upon hotdesking.

The workaround options are:

- Do not use full screen mode on Red Hat.
- Use the -O option to prevent disconnect/reconnect on hotdesking.
- Disable xscreensaver for the server.

Note – Disabling xscreensaver is insecure and may not be the best option.

Bug ID 6383162

Removing a USB disk from a Sun Ray DTU while a Windows application is still accessing it leaves a stale mount point on the Sun Ray server.

Bug ID 6387107

Repeated hotdesking while a Windows Terminal session is active can cause the Sun Ray keyboard to hang on some Linux implementations.

Bug ID 6394230

If the mouse pointer is moved over the Sun Ray Connector window while a user is typing into a window on the Unix/Linux desktop, the keystrokes go to the Connector window, regardless of the Unix/Linux desktop focus behavior settings. (That is, all keystrokes register in the Sun Ray Connector window even if the input focus behavior is set to move to a new window only when the mouse is clicked in that window).

This does not happen if the connector is launched with the **-K** option.

Bug ID 6397952

Sun Ray PageUp/PageDown keys should autorepeat under the RDP client as the equivalent keys on a PC keyboard do.

Bug ID 6404368

Sun Type 6 Japanese keyboards are not detected by default. To correct this condition, invoke **uttsc** or **uttscwrap** with the command line option **-k "sun(type6jp)"**. For example:

```
% uttsc -k "sun(type6jp)"
```

Bug ID 6408886

MS-IME is not enabled when you invoke **uttsc** or **uttscwrap** without any command line options on Japanese locales.

Invoke **uttsc** or **uttscwrap** with the option **-l ja:IME**. For example:

```
% uttscwrap -l ja:IME
```

Bug ID 6421144

If a redirected file contains a square bracket([]) in the file name, then the user cannot perform operations such as delete/rename/copy/move on the file.

Bug ID 6422308

Cut/Copy and paste operations between Windows and Sun Ray applications do not work on Trusted Solaris platforms.

Bug ID 6425188

When users print via the Sun Ray Connector in a Trusted Solaris environment, user access lists for printers are not honored. This issue can be mitigated if printers are configured for a particular label, after which only users at that label have access to the printer.

Trusted Solaris Limitations

Because of user permission restrictions, `uttsc` cannot launch a new audio stream on the Trusted Solaris platform. Instead, it continues to use the default session audio stream. Thus, only one audio application can play on a Trusted Solaris server at any given time.

The following features are not supported on Trusted Solaris platforms at this time for security reasons:

- Disk and serial port redirection
 - Specifying an X display to launch the Sun Ray Connector
-

Windows Limitations

The following features are not supported on Windows 2000:

- Audio
- Drive mapping
- Serial port redirection
- Smart card redirection

Documentation

The most up-to-date versions of documentation for this product are available on docs.sun.com.

L10N Documentation Errata

The following issues were discovered too late to be included in the draft documentation submitted for translation; however, they have been incorporated into the English language documentation in the release image.

Trusted Solaris Configuration

Please perform this additional step before invoking the Sun Ray Connector on Trusted Solaris platforms:

- **Assume primaryadmin role, then add the following privileges to uttsc:**

```
[/etc/security/exec_attr]
...
Sun Ray Connector:tsol:cmd:::/opt/SUNWuttsc/bin/uttsc:uid=
0;privs=4,5,6,10,12,32,33
...
```

Description of Sun Ray Connector Compression

The Sun Ray Connector uses Microsoft Point-to-Point Compression (MPPC) to compress data between the Sun Ray Server, which runs the Sun Ray Connector, and the Windows Terminal Server. The translated versions suggest, less precisely, that data is compressed between the Sun Ray DTU and the Windows Terminal Server.

Description of uttscwrap

The translated drafts imply that `uttscwrap` enables credential caching for all types of authentication. In fact, it enables credential caching for password-based authentication but not for smart card-based authentication. For smart card authentication, please use the Sun Ray Connector directly (`/opt/SUNWuttsc/bin/uttsc`).

